

DUO 4KSN

BROADCASTGEAR Converter DUO 4K SDI+Ethernet

Display indicates status of each in- & output plus fiber connection quality

Video Interface:

- 12G-SDI, 6G-SDI, 3G-SDI, HD-SDI, SD-SDI (auto switching)
- Supports ST2082-1, ST2081-1, ST424, ST292, ST259, ST424, ST292, ST259

Video Standards:

- 4K/UHD 12G/6G / 2160p 23.98/24/25/29.97/30/48/50/59.94/60
- 2K/HD 3G / 1080p 23.98/24/25/29.97/30/48/50/59.94/60
1080i 50/59.94/60
1080PsF 23.98/24/25/29.97/30
720p 23.98/24/25/29.97/30/48/50/59.94/60
- SD 525i/29.97 NTSC, 625i/25 PAL

Connections: / Electrical:

- Optical Fiber Connection: Neutrik OpticalCon DUO
- 1x SDI 3/6/12G Video input
- 1x SDI 3/6/12G Video output
- 2x RJ45 Ethernet 10/100/1Gbps
- 1x XLR4 Power Input 9-48 Volt

Available with following Fiber Connections:

- Neutrik OpticalCon DUO (default)
- Canare SMPTE 311 (FCMR) (Hybrid option available)
- FieldCast 2-Core SM
- Hicon HI-FIBER4
- Others on request



IN	12G	1Gb
OUT	12G	100m
Fiber: -2dB		

