

# CamBack 4K

## BROADCASTGEAR Camera Fiber Converter CamBack 4K

### Video Interface:

- 12G-SDI, 6G-SDI, 3G-SDI, HD-SDI, SD-SDI (auto switching)
- Supports ST2082-1, ST2081-1, ST424, ST292, ST259, ST424, ST292, ST259

### Video Standards:

- 4K/UHD 12G/6G / 2160p 23.98/24/25/29.97/30/48/50/59.94/60
- 2K/HD 3G / 1080p 23.98/24/25/29.97/30/48/50/59.94/60  
1080i 50/59.94/60  
1080PsF 23.98/24/25/29.97/30  
720p 23.98/24/25/29.97/30/48/50/59.94/60
- SD 525i/29.97 NTSC, 625i/25 PAL

### Connections: / Electrical:

- Optical Fiber Connection: Neutrik OpticalCon DUO (optional with SMPTE Hybrid)
- 1x SDI 3/6/12G Video input for Camera Feed
- 1x SDI 3/6/12G Video Camera Loop output
- 2x SDI 3/6/12G Video return (3G maximum when RCU option is installed)
- 2x RJ45 Ethernet 10/100/1Gbps (POE option available)
- 1x Hirose 12p Dataconnection for Camera Control (Only for RCU Option)
- 1x Tally connection (Only for RCU Option)
- Power Input 11-19 Volt (7Watt without camera)
- Hybrid Power Option (Hot Failover)



### Available with following Fiber Connections:

- Neutrik Opticalcon Duo (Hybrid option available)
- Canare SMPTE 311 (Hybrid option available)
- FieldCast 2-Core
- Hicon HI-FIBER4

