

# BaseStation4

## BROADCASTGEAR Base Station 4 Fiber Converter 4K For use with up to four PTZback, CAMback or Converter DUO units

Smart monitor Status display

### Video Interface:

- 12G-SDI, 6G-SDI, 3G-SDI, HD-SDI, SD-SDI (auto switching)
- Supports ST2082-1, ST2081-1, ST424, ST292, ST259, ST424, ST292, ST259

### Video Standards:

- 4K/UHD 12G/6G / 2160p 23.98/24/25/29.97/30/48/50/59.94/60
- 2K/HD 3G / 1080p 23.98/24/25/29.97/30/48/50/59.94/60  
1080i 50/59.94/60  
1080PsF 23.98/24/25/29.97/30  
720p 23.98/24/25/29.97/30/48/50/59.94/60
- SD 525i/29.97 NTSC, 625i/25 PAL

### Connections: / Electrical:

- Optical Fiber Connection: Neutrik OpticalCon DUO (optional with SMPTE Hybrid)
- 4x Dual SDI 3/6/12G outputs
- 4x SDI 3/6/12G Video Input for Return
- 4x SDI 3/6/12G Video Input Loop out
- 1x RJ45 Ethernet 10/100/1Gbps / Internal Gigabitswitch to remote units
- Power Input 90-264VAC 50/60Hz



### Available with following Fiber Connections:

- Neutrik Opticalcon Duo
- Canare SMPTE 311
- FieldCast 2-Core
- Other models on request